



CO-OPM is a full-function optical power meter quick and accurate testing solution for both SM and MM Fiber.

Full set of Connector Interfaces: SC, FC, ST, LC and universal

features:

- 6 Calibrated Wavelengths
- Tone detection
- Data storage function, up to 1000 records
- Reference power level for link loss measurements
- Auto-off and Low battery indication
- AA alkaline and AC adapter for power supply

specifications :

Calibrated Wavelengths	850, 1300, 1310, 1490, 1550, 1625nm
Detector type	InGaAs
Measurement Range	-50°+26dBm
Detector Area	Ø 1.0mm
Uncertainty	±0.15dB 3.5%
linearity	±0.02dB
Display resolution	0.01dB
Frequency ID	270, 330, 1K 2K Hz
Wave ID	850, 1310, 1490, 1550, 1625, 1300nm
Date Storage Capacity	1000
Communication Port	USB
Optical Connector type	FC, SC, ST, LC, 1.25/2.5mm Universal
Alkaline battery	3 x AA 1.5V
Power Supply Adaptor	8.4V
Battery Operating time	200 hr
Operation Temperature	-10° +60° C
Storage Temperature	-25° +70° C
Dimensions h / w / d	200 x 90 x 50mm
Weight	1 lb

Order Information:

CO-OPM	Optical Power Meter
CO-CASE	Protective hard case